



# AUTOGEAR OIL SYN 75W-85

## Product Description:

**AUTOGEAR OIL SYN 75W-85** is an universal high performance fuel saving transmission on synthetic technology for use in manual shifted transmission of the modern passenger car and light vans where an API GL-5, SAE 75W-85 is recommended.

**AUTOGEAR OIL SYN 75W-85** is based on special selected high performance synthetic base oil in combination with a special selected EP-additive package to reach to following properties:

- Excellent EP-properties.
- Excellent thermal- and oxidation stability.
- Good shifting even at low temperatures.
- Low pour point.
- Fuel saving properties.
- Excellent protection against the forming of foam, corrosion and wear.

**AUTOGEAR OIL SYN 75W-85** meets the following performance criteria:

**API GL-5**      **MB 235.7**      **ZF TE-ML 18**      **VW G 052 190**      **VW G 055 190**  
**Alfa-Romeo**    **BMW**            **Fiat**                **Lancia**              **VW G 052 145**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	75W-85
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	870
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	81.4
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	12.2
Viscosity Index		ASTM D2270	146
Brookfield @-40°C	cP	ASTM D2983	150000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-51

**Product Nr:** 43340

**Date Superseded:** 08-12-2017

**Date Issued:** 13-12-2019

**Revision nr:** 01